



## About HIC Conveyor Skirtboard Rubber

ISO 9001 certified HIC International, 1988 formed company, Delhi based Indian producer of **Materials-Spill Safe Sealing Skirt, Rubber Skirting Belt Conveyor Accessories**, exporting to industries in Asia, Europe, Africa, Oceania, America to customer's thorough satisfaction.

Full-proof **Quality Assurance Plan** details on: [www.UniversalDelhi.org](http://www.UniversalDelhi.org)


**Credentials** of Quality World-wide Supplies details on: [www.Rubber-Steel-Industrial-Products.com](http://www.Rubber-Steel-Industrial-Products.com)

**Range** of Tailor-made **Conveyor Sealing Products** Manufacturing details on: [www.hicRubber.com](http://www.hicRubber.com)

# SAFE SKIRTBOARD-SEAL



As per ASTM D412



Rolls per ISO 868



Skirt Rubber Fitting



**Vendor Data** for Supplier Enlistment information on: [www.hicConveyors.com](http://www.hicConveyors.com)

Follow us:



## Why Choose HIC UNIVERSAL Rubber Skirting?

**Abrasion Resistant Rubber Sealing At Conveyor Transfer Points**  
Prevents Falling Materials from Belt Thus Increases Productivity

**Good Sound Protection and Dust Minimizer Under Feed Chute**  
Foolproof Spill-Stop in Various Environments from Iron Ore to Wet Clay

**Lowest Coefficient of Friction Strip**  
Helps Avoiding Aggregate Feeder Belt Damages



### MANUFACTURING RANGE:

NR/SBR/EPDM, up to 16 mm Thick & 400 mm W, as per ASTM D412  
Diamond/Herringbone/Plain, up to 15 mm Thick & 1.2 m W, as per ISO 1629



Technical Specifications download from: [www.hic-india.com](http://www.hic-india.com)

RFQ **skirting rubber rolls** specs. As stated below, in English language please, to quote price offer.

1. Size of Skirtboard rubber (width x length) MM
2. Thickness mm
3. Shore Hardness
4. Quantity Meters or Numbers

